



- \*With vibrating Finished surface.
- \*Zinc plated or chrome plated is an acceptable process.
- \*pplicable for clean rooms, automatic equipment, conveying equipment, and aluminum extrusion equipment.
- \*English unit available, please contact us.

Item Number	Screw Material	Plate Diameter D mm	Plate High L mm	Screw Specification D1 mm	Screw Length L1 mm	Total High H mm	Load Capacity Kg			
E005-50-10-050	SUS304 Stainless	50	21	M10*P1.5	50	71	150			
E005-50-10-100			21	M10*P1.5	100	121	150			
E005-50-12-050			22	M12*P1.75	50	72	200			
E005-50-12-075			22	M12*P1.75	75	97	200			
E005-50-12-100			22	M12*P1.75	100	122	200			
E005-70-12-075		70	70	27	M12*P1.75	75	102	300		
E005-70-12-100				27	M12*P1.75	100	127	300		
E005-70-12-150				27	M12*P1.75	150	177	300		
E005-70-16-050				30	M16*P2.0	50	80	400		
E005-70-16-075				30	M16*P2.0	75	105	400		
E005-70-16-100				30	M16*P2.0	100	130	400		
E005-70-16-150				30	M16*P2.0	150	180	400		
E005-70-20-100				33	M20*P2.5	100	133	400		
E005-70-20-150				33	M20*P2.5	150	183	400		
E005-100-20-100				100	100	37	M20*P2.5	100	137	700
E005-100-20-150		37	M20*P2.5			150	187	700		
E005-100-24-100		36	M24*P3.0			100	136	800		
E005-100-24-150		36	M24*P3.0			150	186	800		
Z005-50-10-050		SS41 Zinc	50	21	M10*P1.5	50	71	150		
Z005-50-10-100				21	M10*P1.5	100	121	150		
Z005-50-12-050	22			M12*P1.75	50	72	200			
Z005-50-12-075	22			M12*P1.75	75	97	200			
Z005-50-12-100	22			M12*P1.75	100	122	200			
Z005-70-12-075	70		70	27	M12*P1.75	75	102	300		
Z005-70-12-100				27	M12*P1.75	100	127	300		
Z005-70-12-150				27	M12*P1.75	150	177	300		
Z005-70-16-100				30	M16*P2.0	100	130	400		
Z005-70-16-150				30	M16*P2.0	150	180	400		
Z005-70-20-100				33	M20*P2.5	100	133	400		
Z005-70-20-150				33	M20*P2.5	150	183	400		
Z005-100-20-100				100	100	35	M20*P2.5	100	135	700
Z005-100-20-150						35	M20*P2.5	150	185	700
Z005-100-24-100						37	M24*P3.0	100	137	800
Z005-100-24-150	37		M24*P3.0			150	187	800		